

RL5NS+

L-5



TAKE ON AGGRESSIONS AND REDUCE DOWNTIME

- **Extra deep lug tread**

Benefit: Superb cut and impact resistance, maximum wear capability, excellent traction.

- **Structure enhanced with high tensile steel belt package and solid centerline section**

Benefit: Ideal structure to take on aggressions and heavy load easily and to sustain longer wear life in quarrying and mining.

- **Extra heavy sidewalls and square shoulders**

Benefit: The square shoulder design pushes debris aside and protects the sidewalls from cuts and damages; The extra heavy sidewalls resist cut and snags.



Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Standard Inflation Pressure (kPa)	Type
				in	mm	in	mm	32nds	mm			
20.5R25	★★	L-5	17.00/2.0	20.47	520	61.02	1550	96	76.5	193A2	600	TL
23.5R25	★★	L-5	19.50/2.5	23.43	595	65.94	1675	107	85	201A2	600	TL
26.5R25	★★	L-5	22.00/3.0	26.57	675	70.87	1800	120	95	209A2	600	TL
29.5R25	★★	L-5	25.00/3.0	29.53	750	75.59	1920	120	95	216A2	600	TL
35/65R33	★★	L-5	28.00/3.5	35.00	889	81.77	2077	122	97	224A2	650	TL