



UTLA ADT Tires

The UTECH UTLA is a pattern that is engineered for soft and muddy soil that requires special traction, maneuverability and flotation. With robust casing built in, it is highly retreadable, which greatly brings the total cost of ownership down.



Parts Details Of UTLA ADT Tires

The wide-base multi-block tread pattern offers exceptional traction and flotation:

- The non-directional multi-block tread pattern delivers excellent lateral grip on soft terrain.
- The wide-base tread features larger footprint with lower ground contact pressure, better stability, and excellent mobility.
- The added slanted open tread grooves provide excellent self-cleaning capability.



Improved impact resistance and retread-ability ensured by high quality architecture:

- High tensile steel belt package built in for better impact and puncture resistance.
- The robust casing is designed for higher load capacity, and it makes the tires retreadable, which optimizes tire investment.

Reinforced tread base and thickened sidewall for better cut and puncture resistance:

- Super thick tread base is applied to increase the puncture resistance.
- The sidewall is thickened for better cut resistance and impact.
- Special cut resistance compound is used to increase the life cycle.

Specifications of UTLA ADT Tires

Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Type
				in	mm	in	mm	32nds	mm		
29.5R29	★★	E4/L4	25.00/3.5	29.49	749	79.65	2023	52	41.5	202B/218A2	TL
29.5R29	★★★	E4/L4	25.00/3.5	29.49	749	79.65	2023	52	41.5	206B/223A2	TL
650/65R25	★★	E4/L4	19.50/2.5	25.59	650	59.06	1500	48	38	180B/193A2	TL
750/65R25	★★	E4/L4	22.00/3.0	29.53	750	63.39	1610	54	43	190B/202A2	TL
850/65R25	★★	E4/L4	25.00/3.0	33.54	852	68.50	1740	59	47	196B/207A2	TL
875/65R29	★★	E4/L4	27.00/3.0	34.76	883	74.06	1881	64	51	203B/214A2	TL
875/65R29	★★★	E4/L4	27.00/3.0	34.76	883	74.06	1881	64	51	213B/218A2	TL